



IRIS - WIDESCREEN THIN CLIENT APPLIANCE

Overview

For window displays, in-store advertising, store theming or digital signage, our IRIS series LCD thin client monitors will enhance your retail locations with informative consumer information screens or streaming video. These integrated LCD thin client monitors with a native resolution support of 1366x768 can be shipped with Windows XP Embedded operating system custom built to your specifications.

Specifications

▶ Operating System

Genuine Windows XP Embedded SP-2

▶ Standard Embedded Software

Citrix ICA client, Microsoft RDP
Internet Explorer with Java and Flash player plugin
Windows Media Player
Microsoft .net framework 1.1 / 2.0
Write protected system partition

▶ Processor, RAM and Flash

VIA 1GHz or 2 GHz Processor
512MB DDR-400 SODIMM as standard (1GB Max)
512MB Flash Drive or 40 GB internal hard drive

▶ Graphics

S3G Unichrome 8xIGP supporting 16:9 aspect ratio(1366x768)
Integrated 26" or 32" or 42" Widescreen LCD monitor

▶ I/O Ports

Stereo out, microphone in, PS/2 Keyboard and mouse , RJ45
Ethernet, 9 pin serial port, 25 pin parallel port, 2 x USB 2.0

▶ Power

Input voltage: 100-240 VAC
Input frequency: 50/60Hz

Optional internal 802.11 b/g or Bluetooth wireless

Applications

- Digital signage solutions
- Public information systems

